

Mobil Super ATF 3309

Automatic Transmission Fluid

Mobil Super ATF 3309 is an exceptionally high performance lubricant that meets original equipment manufacturers' specifications for use in certain slip-controlled lock-up automatic transmissions. Mobil Super ATF 3309 is recommended for use in transmissions made by Aisin-Warner requiring a fluid approved against Type T-IV, JWS 3309, GM 9986195 and VW/Audi G-055-025-A2. These Aisin-Warner transmissions are used in CERTAIN domestic and foreign vehicles, including Toyota, Lexus, Audi, Saturn, Ford, Volvo, Volkswagen, Saab, Porsche and Mitsubishi.

Features and Benefits

The unique formulation of Mobil Super ATF 3309 is designed to provide excellent lubrication of transmissions in specified Aisin-Warner slip-controlled lock-up automatic transmissions. These outstanding performance capabilities translate into significant operational benefits, including:

- Excellent lubricating characteristics for quiet operation and smooth shifting in approved transmissions
- Controlled friction properties for smooth and efficient transmission of power across all normal temperature ranges
- Helps to control transmission shudder and provide excellent vehicle driveability
- Helps to extend transmission life based on excellent wear control
- Long fluid life based on excellent oxidation resistance
- Excellent viscosity stability (high viscosity index) to help assure adequate lubrication without excessive thinning in severe high-temperature service or thickening at low starting temperatures
- Resistance to foaming
- Superb protection against rusting and corrosion
- Compatibility with synthetic rubber seal materials

Applications

Mobil Super ATF 3309 is recommended for use in transmissions made by Aisin-Warner requiring fluids approved against JWS 3309 or GM 9986195. It is also recommended for service fill applications where Toyota T-IV, T4, T-III or T3 are called for. Please refer to the owners' manual for proper fluid requirements.

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet, which is available online at www.imperialoil.ca/mobil or by contacting Lubricants and Petroleum Specialties, Technical Services, Technical Help Desk: 1-800-268-3183

© 2001 Imperial Oil
© The Mobil logotype and the Pegasus design are registered trademarks of Exxon Mobil Corporation.
™ Trademark of Exxon Mobil Corporation, Imperial Oil, Licensee.



Specifications and Approvals

MOBIL SUPER ATF 3309 meets the following specifications	Model	Part No. or specification
Audi	TT, A3	G-055-025-A2
Ford	Five Hundred Montego	WSS-M2C924-A
Lexus	Most models	JWS 3309/Type T-IV
Mitsubishi Fuso	FE	2005 and newer vehicles
Porsche	Cayenne S, Cayenne Turbo	JWS 3309/Type T-IV
Saab	9.3, 9.5	All 5-speed automatics
Saturn	Vue, Ion	GM9986195
Toyota	Most models	JW 3309/Type T-IV
Volkswagen	Touareg, Beetle, Cabriolet	G-055-025-A2
Volvo	S60, S70, V70, C70, S80, XC90, S40, V40	All 5-speed automatics

! Check with your dealer or owner's manual

Typical Properties

MOBIL SUPER ATF 3309	
Viscosity	
cSt @ 100°C	7.2
cSt @ 40°C	35
cP @ -40°C	14,000
Viscosity Index	180
Flash Point, °C	>185
Pour Point, °C	< -45
Density	0.8540
Color	Red

Precautions

MOBIL SUPER ATF 3309 is manufactured from high quality base stocks, carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Special care is also recommended in handling used motor oils. A Service Data Sheet entitled "Safe Handling of Used Motor Oils" is available on request from your Imperial Oil Representative. Please refer to our Imperial Oil Material Safety Data Sheet for further information.

Note: This product is not controlled under Canadian WHMIS legislation.

The Mobil logotype, the Pegasus design, and Mobil Super are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

8-2008

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet, which is available online at www.imperialoil.ca/mobil or by contacting Lubricants and Petroleum Specialties, Technical Services, Technical Help Desk: 1-800-268-3183

© 2001 Imperial Oil
 © The Mobil logotype and the Pegasus design are registered trademarks of Exxon Mobil Corporation.
 ™ Trademark of Exxon Mobil Corporation, Imperial Oil, Licensee.

